


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
A		REPLACES REV NEW WITH CHANGE.	98-05-20	Kim Le
		DIRECT UPDATE:	98-05-21	Oscar Lofstrom
		1) REVISED DWG VIEWS TO REFLECT NEW FRONT PANEL ASSY CONFIG.	98-05-21	John Harrenstein
		REASON: 02 SEVERITY: 09	98-05-21	Chanh Tran
B		REPLACES REV. "A" WITH CHANGE	2000-03-10	Ken Troc
		DIRECT UPDATE:	2000-03-16	John Harrenstein
		1) CORRECTED MATING CONNECTOR PART NO. FROM "SCA3D150P1210" TO "SCA3D150P1510". 2) UPDATED DWG FORMAT TO HONEYWELL.	2000-01-16	Gary Sturgis
	REASON: 05 SEVERITY: 09			
C		REPLACES REV "B" WITH CHANGE	2003-2-10	Kim Le
		DIRECT UPDATE:	2003-3-18	John Harrenstein
		1) DELETED "+.010/- .000 CONNECTOR TO BOTTOM OF UNIT" DIMENSION IN ZONE B2 ON SHEET 2. 2) ADDED FLAGNOTE 7 AND ITS CALL-OUT TO SHEET 2. 3) ADDED VIEW A TO SHEET 2.		
	REASON: 05 SEVERITY: 09			

NOTES: UNLESS OTHERWISE SPECIFIED,

- COOLING AIR NOT REQUIRED.
- WEIGHT: 7.5 LBS MAX.
- MINIMUM IDENTIFICATION INFORMATION:  
PART NO. 965-1076-OXX-XXX-XXX  
SERNO:    
MFG DATE:    
TSO-C92c  
TSO-C117a  
ENVIR CAT: DO-160C  
SOFTWARE: DO-178B LEVEL C,D  
MODIFICATION STATUS  

CONFIGURATION DATABASE  
MOD STATUS IF APPLICABLE

APPLICATION S/W MOD  
STATUS IF APPLICABLE
- POWER DISSIPATION IS 26 WATTS WITH NO WARNINGS. 40 WATTS WITH WARNING AND 8 OHM SPEAKER CONNECTED. THE HEATER BLANKET DISSIPATES AN ADDITIONAL 48 WATTS TYPICAL (90 WATTS MAXIMUM) WHEN IT IS ON. THE HEATER BLANKET WILL TURN ON WHEN THE TEMPERATURE INSIDE THE UNIT IS  $\leq -20 \pm 4^{\circ}\text{C}$  AND WILL TURN OFF WHEN THE TEMPERATURE INSIDE THE UNIT IS  $\geq -10 \pm 4^{\circ}\text{C}$ .
- THIS DIMENSION CONTROLS WIDTH OF FRONT PANEL AND IS TO BE MEASURED FROM THE  $2.25 \pm .04$  DIMENSION.
- THE SYMBOL  INDICATES THE CENTER OF GRAVITY OF UNIT.
- THE BOTTOM OF REAR PANEL ASSEMBLY SHALL BE FLUSH TO .010 BELOW THE BOTTOM SURFACE OF CHASSIS AS SHOWN IN VIEW A.

### INTERFACE CONTROL DRAWING

Typed names constitute approval. Actual signatures on file at Honeywell in Redmond Wa.

This document is an unpublished work. Copyright 1998,2003 Honeywell International Inc. All rights reserved

This document and all information and expression contained herein are the property of Honeywell International Inc, and is provided to the recipient in confidence on a "need to know" basis. Your use of this document is strictly limited to a legitimate business purpose requiring the information contained therein. Your use of this document constitutes acceptance of these terms.

	C	C
	B	B
	A	A
	-	-
SHEET	1	2
REVISION STATUS OF SHEETS		

-201	960-2224	960-2224
DASH NO.	NEXT ASSY	USED ON
APPLICATION		

MATERIAL	UNLESS OTHERWISE SPECIFIED	CONTRACT NUMBER	
	ALL DIM. ARE IN INCHES	DRAWN	K.L.
	TOL .XX ± —	CHECK	J.H.
	.XXX ± —	ENGR	D.K.
	ANGLE ± —	MFG	C.T.
	INTERPRET DRAWING PER DOD-STD-100.	QA	O.L.
	BREAK-ALL SHARP EDGES	APPD	
	SURFACE-ROUGHNESS ✓		
PRECIOUS METAL INDICATOR CODE: NA			

Honeywell International Inc. Redmond, Washington 98073-9701		<b>Honeywell</b>	
DWG TITLE			
EGPW SYSTEM, 28 VDC, OUTLINE			
SIZE	CADE CODE	DWG NO.	REV.
D	97896	960-2224-201	C
SCALE 1/1	WT.	SHEET 1 OF 2	H-DFORM/REV-A

MKVII EGPWS

